# **INTEGRITY® ANTISTATIC PINK FINGER COTS**

602-4015

Integrity® Pink Antistatic Fingercots ISO 5 Cleanroom Compatible. Average surface resistivity is 1012 Ohm /sq. and average decay charge rate is <2 seconds. For use with CLASS II/CATEGORY B static sensitive device with a threshold sensitivity above 1000V(≥1000V), packaged in an electro-static shield bag for more protection from static charges. Non-Sterile.

#### **MATERIAL**

100% Pure Natural Latex

THICKNESS	LENGTH	ELONGATION	TENSILE STRENGTH
5 Mils (0.127mm)	2.55~ 2.95 inches (64.7 ~74.9 mm)	761%	4.5 lbs/inch <sup>2</sup>

#### COLOR

Pink

## **PACKAGING**

Packaged in an electro-static shield bag for further protection against static charges.

PRODUCT CODE	SIZE	DIAMETER
602-4015	Small	0.62 in (16mm)
602-4016	Medium	0.70 in (18mm)
602-4017	Large	0.78 in (20mm)
602-4018	X-Large	0.86 in (22mm)

### **QUANTITY**

5 Gross/Pack, 720 pcs/pack. 200 Gross/case, 28,800 pcs/case.





IMPORTANT: This data sheet and its contents (the "Information") belong to Integrity Cleanroom or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Integrity Cleanroom assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Integrity Cleanroom was aware of the possibility of such loss or damage arising) is excluded. © Integrity Cleanroom.



Integrity US Round Rock, Texas











