

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISS	UE	NUMBER
ORIGINAL		

(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED

COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:


.X ±0.25 .XX ±0.13 .XXX ±0.05

POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 20A (CURRENT) 5000MΩ min.

1000V AC rms

-55°C ~ 125°C



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY			
COMBIN			DATE: JAN. 01/20	19		
			DATE:			
	C THESE DRAWINGS AND SPECIFICATION	1 SCALL. (IN C.A.D. 1.1)	SHEET 1 OF	2		
	OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-11W	DRAWING NUMBER: 629-11W1250-2N3			
YOUR CONNECTION TO QUALITY & SE	RVICE MANUFACTURE OR SALE OF APPARAT WITHOUT WRITTEN PERMISSION.		/1250-2N3	1		



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

