Mallory Sonalert Products, Inc. Sales Outline Drawing				Part #:	JT	JT028-RYG-CSL	
				Revision: C			
Specifications:							
Stack Number:	1	2	3			-	
LED Color:	RED	YELLOW	GREEN				
Connection Wires:	Red and Brown	Yellow and Brown	Green and Brown				
LED Current Draw:	<50 mA	<60 mA	<40 mA				
Rated Voltage:	200 III/A	100 III/1	24 VAC/DC	1		<u> </u>	
Operating Voltage:			20-28 VAC/DC	^			
Sound Level Category:	Loud	Loud	Loud	<u> </u>		Loud	
Sound Level Category.	Loud	Medium Pulse	Loud		Continuous for 5 sec then 0.1s beep until		
Mode of Operation:	Continuous	(5PPS)	Double Pulse (0.	reset			
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wirk wire connected to Gray wire				
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max		40mA Max.		
Loudness @ 1m:			80-85 dB(A) Ty		•		
Frequency:	2000 ± 500 Hz						
Total Max Current:	<190mA with all LED's and sound unit working						
Operating Temperature:	-25° ~ +60°C						
Lens Color:	Opaque White						
Material:	ABS FR15U						
Mounting Method:	Stainless Steel Pole						
Weight Typical (g):	730						
NEMA 12:	Approved						
Options:	Approved Please contact factory.						
Dimensions: Inches (mr	n)	CUL Recogr PATENT NUMBER	1 0309594			ROHS Complian	
RED 6.7 [169.8]	FREEN			GΑ	ASKET	48° wire	
-		-19.6 [497.6]	Øn.	20 [ø5.2]	Ø0.57 [Ø1	[4.6]	
2.4 [61.8] — 2.7 [68.3] — TOP VIEW	3)			places 9	2.04 0.95 [2	[51.9]	
		E TO POWER AND BE			IND		
SOUND OPERATION:		ID BLACK WIRES TO F				ODEENIA/ELLOW/WIDE	
	FOR DOUBLE PULSI	E, CONNECT GRAY &	BLACK TO POWER A	ND PURPL	E WIRE TO	GREEN/YELLOW WIRE. GREEN/YELLOW WIRE. O GREEN/YELLOW WIRE.	