

## Specification Sheet

Part Number: 170-03097



Braided Sleeving, Aluminum Laminated Fiberglass, 2.5" Dia, AL/GF, Silver, 50 ft/reel

**Article Number**

170-03097

**Type**

BSHTTST212SR

**Color**

Silver (SR)

**Features & Benefits**

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

**Quantity Per**

reel

**Product Description**

High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

<b>Short Description</b>	Braided Sleeving, Aluminum Laminated Fiberglass, 2.5" Dia, AL/GF, Silver, 50 ft/reel
<b>Global Part Name</b>	BSHTTST212SR-AL/GF-ML
<b>Length L (Imperial)</b>	50.0
<b>Length L (Metric)</b>	15.2
<b>Bundle Diameter Min (Imperial)</b>	0.1
<b>Bundle Diameter Min (Metric)</b>	2.54
<b>Bundle Diameter Max (Imperial)</b>	2.375
<b>Bundle Diameter Max (Metric)</b>	60.3
<b>Diameter D (imperial)</b>	2.5
<b>Diameter D (metric)</b>	63.5
<b>Nominal Diameter (Imperial)</b>	2-1/2
<b>Nominal Diameter (Metric)</b>	63.5
<b>Wall Thickness WT (Imperial)</b>	0.025
<b>Wall Thickness WT (Metric)</b>	0.64
<b>Material</b>	Aluminum (AL) Glass Fiber (GF)

**Material Shortcut**

AL GF

**Flammability**

Non-Flammable

**Halogen free**

Yes

**Operating Temperature (Metric)**

-76°F to +491°F (-60°C to +255°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

50

**Package Quantity (Metric)**

15.24

**Customs Number**

7019905050

**Weight (Metric)**

2.3

**Weight (Imperial)**

5.05