



Click [here](#) for the 3D model.

| Dimensions |                |
|------------|----------------|
| D          | 30mm +1mm      |
| L          | 30mm +2mm      |
| S          | 10mm +/-0.5mm  |
| LL         | 5.8mm +/-1mm   |
| F          | 1.5mm +/-0.1mm |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 200       |

| General Information |                                |
|---------------------|--------------------------------|
| Series              | ELH                            |
| Dielectric          | Aluminum Electrolytic          |
| Description         | Snap-In, Aluminum Electrolytic |
| RoHS                | Yes                            |
| Lead                | 2 Pin                          |
| AEC-Q200            | No                             |

| Specifications        |                           |
|-----------------------|---------------------------|
| Capacitance           | 6,800 uF                  |
| Capacitance Tolerance | 20%                       |
| Voltage DC            | 50 VDC, 63 VDC (Surge)    |
| Temperature Range     | -40/+85°C                 |
| Rated Temperature     | 85°C                      |
| Life                  | 2000 Hrs                  |
| Dissipation Factor    | 30% 120Hz 20C             |
| Resistance            | 0.0585 Ohms (120 Hz 20°C) |
| Ripple Current        | 3800 mAmps (120Hz)        |
| Leakage Current       | 3000 uA (5min 20°C)       |