ATGBICS FTLX3671DTC45 Finisar Compatible Transceiver DWDM Ch45 SFP+ 1.2 to 11.3GBase (1541.35nm, SMF, 40km, LC, DOM, Ind Temp)

Brand : ATGBICS

Product name : FTLX3671DTC45 Finisar Compatible Transceiver DWDM Ch45 SFP+ 1.2 to 11.3GBase (1541.35nm, SMF, 40km, LC, DOM, Ind Temp)

FTLX3671DTC45 Finisar Compatible Transceiver DWDM Ch45 SFP+ 1.2 to 11.3GBase (1541.35nm, SMF, 40km, LC, DOM, Ind Temp)

ATGBICS FTLX3671DTC45 Finisar Compatible Transceiver DWDM Ch45 SFP+ 1.2 to 11.3GBase (1541.35nm, SMF, 40km, LC, DOM, Ind Temp). SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box





Performance		Power	
SFP transceiver type * Fiber optic	10000 Mbit/s	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Coarse Wavelength Division Multiplexing (CWDM)	ber optic connector LC FP transceiver standard DWDM aximum transfer distance 40000 m lavelength 1541.35 nm barse Wavelength Division Image: CWDM ultiplexing (CWDM) Image: CWDM thernet LAN Image: CWDM thernet interface type 10 Gigabit Ethernet igital Diagnostics Monitoring Image: CWDM	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 °C 85 °C -40 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
Ethernet LAN		Weight & dimensions	
Ethernet interface type Digital Diagnostics Monitoring (DDM)		Width Depth Height	13.4 mm 56.5 mm 8.5 mm
Features		Weight	19 g
Product colourSilverHousing materialMetalPlug and Play✓Hot-swap✓		Packaging data	
		Number of products included Package type	1 pc(s) Box
Easy to install	· ·	Technical details	
Country of origin Brand compatibility Certification	United Kingdom Finisar CE, FCC, RoHS	Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead
	, ·, · · · · ·		

Product code: FTLX3671DTC45-C



5056468764218

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.