

Note: This datasheet may be out of date. Please download the latest datasheet of GCM0335C1E120FA16# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en-us/products/productdetail?partno=GCM0335C1E120FA16%23

## GCM0335C1E120FA16D



< List of part numbers with package codes > GCM0335C1E120FA16D GCM0335C1E120FA16W

### Applications

Please be sure to read and comply with		
these "Precautions for use."		
Automotive powertrain/safety equipment,		
Automotive infotainment/comfort		
equipment,Medical equipment [GHTF		
A/B/C] except for implant equipment		
Please refer to Our Website and		
specifications, etc. for information about		
the performance, functions, quality,		
management, and safety required for		
the above applications, and use		
Products after confirming the		
performance and reliability of the actual		
Product.		

#### GCM0335C1E120FA16J




# References

Packaging	Specifications	Standard Packing Quantity
D	φ180mm Reel Paper Tape	15000
W	φ180mm Reel W8P1 Paper Tape	30000
J	φ330mm Reel Paper Tape	50000

Mass (typ.)		
1 piece	0.33mg	

### Appearance & Shape





1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GCM0335C1E120FA16D

Note: This datasheet may be out of date. Please download the latest datasheet of GCM0335C1E120FA16# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GCM0335C1E120FA16%23

#### "#" indicates a package specification code.



### Specifications

Length	0.6±0.03mm
Width	0.3±0.03mm
Thickness	0.3±0.03mm
Capacitance	12pF ±1%
Distance between external terminals g	0.2mm min.
External terminal size e	0.1 to 0.2mm
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	25Vdc
Size code in inch(mm)	0201 (0603M)
TC	0±30ppm/°C
Temperature characteristics (complied standard)	C0G(EIA)
Temperature range of temperature characteristics	25℃ to 125℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.