

## Specification Sheet

Part Number: 117-00012



Wide strap minimizes pinching of soft hoses and convoluted tubing.  
Clamping rails increase circumferential grip on varying bundle diameters.

Locking stud mount pawls allow for easy hand insertion.

Nut or weld nesting counterbore provides flush mounting at the base.

Stand Off Dual Clamp Tie, 20.10" Long, .31" Stud Dia, PA66HIRHSUV, Black, 250/pkg

**Article Number** 117-00012

**Type** SDCTR312

**Color** Black (BK)

**Quantity Per** carton

**Product Description** Stand Off Dual Clamp Ties offer the same features as the standard dual clamp tie, with a standoff mount that secures the bundle away from the side of the frame rail. This protects the bundles from bolts and other protrusions.

**Short Description** Stand Off Dual Clamp Tie, 20.10" Long, .31" Stud Dia, PA66HIRHSUV, Black, 250/pkg

**Global Part Name** SDCTR312-PA66HIRHSUV-BK

<b>Minimum Tensile Strength (Imperial)</b>	100
<b>Minimum Tensile Strength (Metric)</b>	445
<b>Length L (Imperial)</b>	20.1
<b>Length L (Metric)</b>	510.5
<b>Fixation Method</b>	Weld Stud Fixing
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.7
<b>Bundle Diameter Min (Imperial)</b>	0.375
<b>Bundle Diameter Min (Metric)</b>	9.5
<b>Bundle Diameter Max (Imperial)</b>	2.3
<b>Bundle Diameter Max (Metric)</b>	58.4
<b>Height H (Imperial)</b>	1.47
<b>Height H (Metric)</b>	37.30

<b>Stud Diameter (Metric)</b>	M8
<b>Stud Diameter (Imperial)</b>	5/16
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	250
<b>Package Quantity (Metric)</b>	250
<b>Customs Number</b>	3926909988