


HT55AN103GN

Obsolete

HP LDD Indust COG HT200C, Ceramic, 0.01 uF, 2%, 25 VDC, COG, Commercial, High Temperature, Lead Spacing = 5.08mm



Click here for the 3D model.

Dimensions	
L	5.08mm MAX
Н	5.08mm MAX
Т	2.54mm MAX
S	5.08mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm
G	1.65mm MAX

Packaging Specifications

Packaging Waffle, Tray

General Information		
HP LDD Indust COG HT200C		
Radial		
Commercial, High Temperature		
LDD High Temperature 200C		
No		
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
Nickel		
No		

Specifications			
Capacitance	0.01 uF		
Capacitance Tolerance	2%		
Voltage DC	25 VDC		
Temperature Range	-55/+200°C		
Temperature Coefficient	COG		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.