T	Q		г		т		D		0		₽	A		
		V Thread												4
در									LAYOU	IT SHOWN AS EX	AMPLE			3
			Keying Showr	as example										
CHARACTERISTICS				Connect	tor dimension	1								
	MIL-DTL-38999 Series III			Dim ØS	Nominal 25 Max									
-Shell Material -Shell Plating -Insulator -Contacts	: Composite : Without Plating : Thermoplastic : Copper Alloy			Z VV THREAD	31 Max M15x1-6g]			due to a use of t the Specifications iss	he Products whi ued by either of	non-conformity or d ich does not comply the Parties or by a th on, technical notice.)	with iird party		
-Seals & Grommet	: Silicon Elastomer									Country FR		& Control List		2
-Durability	Contact Plating : Gold over copper Alloy 0.8μm minimum Durability : 500 Mating cycles Delivered without Souriau contacts					FR Not Listed PN: 8D511X01PNL								
-Temperature Range	-						A 18-1	10-2016 Fi	rst Release					
-Salt Spray — -Mass	: 2000 hours : 12.1 g ± 10%								Latest modification -	by			MOD N°	
							Designed By:		Date:	-	CUS	STOMER DRAWING	1	
							TITLE			Composite Plug 8D series				
BASIC SERIES:	8D 5	- 11 X	01 P N	L	Delivered W/	/O Contacts	SCALE NA			General linear Tolerances: ±	Ν	NPRDS / PROJECT 859		
	tandard Crimp Contact			C		ITATION : N	SOUR	RIAU	WWW.S	DURIAU.C		This document is the pro SOURIAU it must not be reproduc communicated without pe	ced or	
PLATING : X =	Without Plating		L		CONTACT LAYO		FORMAT		9	OURIAU			SHEET	-
		I			_		A3			8D511X0			1/2	
1	G	I	F		E	1	D		С		В			_

-	Ŧ	G	г – – –	m	D	0
		Contact Layout				
4	/	01				
	(1#12				
	Ctc A	11-01 X Y 0 0				
ω						
						SOURIAU shall not be liable for any
						due to a use of the Products wh the Specifications issued by either of (professional recommendat
N						PN: 8D511X
					A 18-10-2 ISS DATE	016 First Release
					Designed By:	Latest modification - by Date: Compo
_					SCALE NA	General linear Tolerances: ±
					SOURIA	
		1	1		FORMAT A3	SOURIAU 8D511X0
	Н	G	F F	E	D	C

