


C907U150JZSDCA7317

Not for New Design

C900AC SFTY X1-440 Y2-300, Ceramic, 15 pF, 5%, 440 VAC (X1), 300 VAC (Y2), SL, Lead Spacing = 7.5mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	
Series	C900AC SFTY X1-440 Y2-300
Style	Radial Disc
RoHS	Yes
Termination	Tin
Failure Rate	N/A
Qualifications	UL, ENEC, VDE, CSA, CAN
AEC-Q200	No
Halogen Free	Yes
Component Weight	400 mg

Specifications	
Capacitance	15 pF
Capacitance Tolerance	5%
Voltage AC	440 VAC (X1), 300 VAC (Y2)
Dielectric Withstanding Voltage	2600 VDC
Temperature Range	-40/+125°C
Temperature Coefficient	SL
Insulation Resistance	10 GOhms
Quality Factor	700
Safety Class	X1/Y2

~				~-	
(lick	here	tor	the	KI)	model

Dimensions		
D	7mm MAX	
Т	5mm MAX	
S	7.5mm +/-1mm	
НО	18mm +2/-0mm	
F	0.55mm +/-0.1mm	

Packaging Specifications				
Packaging	Ammo			
Packaging Quantity	1000			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.