

# Han Gigabit insert M Cat. 7 (shield-GND)



Part number	09 14 008 3032
Specification	Han Gigabit insert M Cat. 7 (shield-GND)
HARTING eCatalogue	https://b2b.harting.com/09140083032

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Inserts
Specification	Han <sup>®</sup> Gigabit insert
Features	Suitable for PoE++

#### Version

Termination method	Crimp termination
Gender	Male
Number of contacts	8
further contacts	+ shielding
	With additional shield connection to the hinged frame
Details	Please order crimp contacts separately.
	Please order adapter module separately.

## Technical characteristics

Conductor cross-section	0.09 0.52 mm²
Rated current	5 A
Rated voltage	50 V
Rated voltage	50 V AC 60 V DC
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	30 V
Transmission characteristics	Cat. 7 <sub>A</sub> Class F <sub>A</sub> up to 1,000 MHz



## Technical characteristics

Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Contact resistance, shielding	≤100 mΩ
Limiting temperature	-40 +85 °C
Mating cycles	≥500

# Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (shielding)	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
ECHA SCIP number	1e38d35d-d1be-4585-8e03-95faccd739bf
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead

# Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

#### Commercial data

Packaging size	1
Net weight	36 g

Page 2 / 3 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany

Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Product data sheet 09 14 008 3032 Han Gigabit insert M Cat. 7 (shield-GND)



## Commercial data

Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440218 Module for industrial connectors (data)