1	2	3	4	5		
9 9 9 9 9 9 9 9 10 $0,9$ $0,9$ 10 $0,9$ $0,9$ 10 $0,9$ $0,9$ 10 $0,9$ $0,9$ 10 $0,9$	51E 0,9 15,5 10,7 11,8 0,9 15,5,5,5 15,5,5,5 15,5,5,5 15,5,5,5,5 15,5,5,5,5 15,5,5,5,5,5,5,5,5,5,5,5,5,5,5,5,5,5,5,	2,5 Ø1	1,5 TECHNICAL CHARACTI MATERIAL INSULATOR: PA6/66 FLAMMABILITY RATING COLOR: GREEN METAL HOUSING: COP TERMINAL SCREW: ST WIRE GUARD: COPPEF ENVIRONMENTAL OPERATING TEMPERA COMPLIANCE: LEAD FF ELECTRICAL CURRENT RATING: WORKING VOLTAGE: WITHSTANDING VOLTA CONTACT RESISTANCE STANDARD MECHANICAL SOLID WIRE: 31	ERISTICS ERISTICS ERISTICS EL / Zn RALLOY / Ni+Sn EEL / Zn RALLOY / Ni+Sn TURE: -30°C UP TO +120°C REE AND ROHS UL VDE 16 A 24 A 300 VAC 750 VAC GE: 1,6 KV 3 KV E: 20 mΩ MAX P31 CAT. N°: MRT6 (3) 1395 TYPE: MRT6 D-12 AWG / 0,05-3,31 mm ² 5 Lb.In / 0,5 Nm F 6 mm		В
	Ţ	691 233 810 102				
RoHS Compliant G	PROJECTION:	GENERAL TOLERANCE				-
F E		±0,1				Η
D						
C	APPROVAL: FBr		DESCRIPTION: SERIE 2338 - 10.00 MM - HOP RISING CAGE CLAMP - WR-TBL	RIZONTAL CABLE ENTRY WITH	SIZE	D
B A 18-FEB-16 PDF	AK	SCALE: SHEET: 1/2	WERI PART NO: 691 233 810 0xx		A4	
	/ 11.		THEIRIT AIRT NO. 031 203 010 0AA			1 1

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONIK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	Ъ
В					SCALE:			Γ
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			