

230V Automatic Voltage Switch with Surge Protection, 380 Joules, Hardwired

MODEL NUMBER: AVS30D











Highlights

- 30-amp current rating
- Hardwired directly into home and office mains
- Over- and undervoltage protection
- · Surge and spike protection

Package Includes

- AVS30D Automatic Voltage Switch
- Owner's manual

Description

AVS30D Automatic Voltage Switch is a complete power protection device combining overvoltage, undervoltage, lightning and spike/surge protection for your appliances and electronics. Also guards against surges and spikes that may occur when power is restored. Hardwired directly into home or office wiring, the AVS30D safeguards refrigerators, freezers, air conditioners, washers, dryers, TVs and computer equipment from fluctuating power.

Program buttons let you quickly set voltage range, on/off delay, overload protection and digital display mode, The easy-to-read digital LED displays show you voltage, wattage, settings and status at a glance, The AVS30D features surge-protecting components to guard against spikes and surges.

Features

- 30-amp current rating
- Input terminal connects to the mains power
- Output terminal connects to home or office wiring
- Program buttons
- Voltage LED
- Load LED
- Digital LED display

Specifications

OVERVIEW	
UPC Code	037332182142





Output Proceptacles Hardwire Output Amp Capacity 30 Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 220 V AC Recommended Electrical Service 230 V Voltage Compatibility (VAC) 290 Maximum Surge Amps 6500KA Input Plug Type Hard-wire Input Cord Length (ft) 0 Right-Angle Plug No Integrated Cord Clip No Integrated Cord Clip No SURGE / NOISE SUPPRESSION* SURGE / NOISE SUPPRESSION* AC Suppression Joule Rating 380 AC Suppression Response Time <1ns ALIO Shut-Off No DATALINE SURGE SUPPRESSION* Telephone/DSL Protection No Network (Ethernet) Protection No <			
Output Amp Capacity 30 Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 220V AC Recommended Electrical Service 230V Voltage Compatibility (VAC) 230 Maximum Surge Amps 6500KA Input Plug Type Hard-wire Input Plug Type No Right-Angle Plug No Input Cord Length (ft.) 0.00 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS USER INTERFACE, ALERTS & CONTROLS Surger Noise Suppression AC Suppression Joule Rating 380 AC Suppression Response Time <1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coay) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black		Hardwire	
Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 220V AC Recommended Electrical Service 230V Voltage Compatibility (VAC) 230 Maximum Surge Amps 6500kA Input Plug Type Hard-wire Input Cord Length (ft.) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time <1ns			
Nominal Input Voltage(s) Supported 220V AC Recommended Electrical Service 230V 230V			
Nominal Input Voltage(s) Supported 220V AC Recommended Electrical Service 230V Voltage Compatibility (VAC) 230 Maximum Surge Amps 6500kA Input Plug Type Hard-wire Input Cord Length (ft.) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time <1ns	Tright Angle Oddets		
Recommended Electrical Service 230V Voltage Compatibility (VAC) 230 Maximum Surge Amps 6500kA Input Plug Type Hard-wire Input Cord Length (It.) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No VSER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time < 1ns Auto Shut-Off No PATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Elack	INPUT		
Voltage Compatibility (VAC) 230 Maximum Surge Amps 6500kA Input Plug Type Hard-wire Input Cord Length (ft.) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time -1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Nominal Input Voltage(s) Supported	220V AC	
Maximum Surge Amps 6500kA Input Plug Type Hard-wire Input Cord Length (ft.) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time <1ns	Recommended Electrical Service	230V	
Input Plug Type Hard-wire Input Cord Length (ft.) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No WEER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time < 1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Voltage Compatibility (VAC)	230	
Input Cord Length (ft.) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time < 1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Maximum Surge Amps	6500kA	
Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time < 1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Input Plug Type	Hard-wire	
Integrated Cord Clip No Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time < 1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Input Cord Length (ft.)	0	
Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time <1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Right-Angle Plug	No	
USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time <1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Input Cord Length (m)	0.00	
Diagnostic LED(s) SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time <1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Integrated Cord Clip	No	
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 380 AC Suppression Response Time 41ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Black	USER INTERFACE, ALERTS & CONTROLS		
AC Suppression Joule Rating 380 AC Suppression Response Time <1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Diagnostic LED(s)	Yes	
AC Suppression Response Time <1ns Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black			
Auto Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	AC Suppression Joule Rating	380	
DATALINE SURGE SUPPRESSION Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	AC Suppression Response Time	<1ns	
Telephone/DSL Protection Yes Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Auto Shut-Off	No	
Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	DATALINE SURGE SUPPRESSION		
Network (Ethernet) Protection No PHYSICAL Anti-Microbial Protected No Color Black	Telephone/DSL Protection	Yes	
PHYSICAL Anti-Microbial Protected No Color Black	Cable (Coax) Protection	No	
Anti-Microbial Protected No Color Black	Network (Ethernet) Protection	No	
Color Black			
	Anti-Microbial Protected	No	
Housing Color Black	Color	Black	
	Housing Color	Black	
Integrated Keyhole Mounting Slots No		No	
Material of Construction Plastic		Plastic	
Shipping Dimensions (hwd / cm) 6.10 x 13.21 x 23.37	Shipping Dimensions (hwd / cm)		



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Shipping Dimensions (hwd / in.)	2.40 x 5.20 x 9.20	
Shipping Weight (kg)	0.54	
Shipping Weight (lbs.)	1.20	
Unit Dimensions (hwd / cm)	17.78 x 13.31 x 5.537	
Unit Dimensions (hwd / in.)	7 x 5.24 x 2.18	
CERTIFICATIONS		
Certifications	CE	
Approvals	RoHS	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies