


LF-260N KEMET, LF, EMI/RFI Filters, Noise Suppression, 250 VAC



General Information	
Series	LF
Style	Metal Box
Description	Metal Box
Features	Large Current
Phase	Three-phase
RoHS	With Exemptions
SCIP Number	10661cea-adfc-45e6-be80-e6b4fd31a87d
Notes	DC Available.
Miscellaneous	30 K Self-Temperature Rise Max.

Specifications	,	
Voltage AC	250 VAC	
Voltage	1500 VAC Withstanding Voltage 1 Min. Line to Ground	
Rated Current	60 A (AC/DC)	
Rated Temperature	45°C	
Temperature Range	-20/+55°C	
Leakage Current	1 mA MAX (250 V 60 Hz)	
Resistance	300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground	

Click here for the 3D model.

Dimensions		
L	315mm MAX	
W	130mm MAX	
н	90mm MAX	

Packaging Specifications		
Packaging	Tray, Box	
Packaging Quantity	2	
Component Weight	6500 g	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Aliases (UNFLF260NXXXXX)