

RC-06S1N12Z500 - 1593993

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Cable connector, with Pg9 connection thread, angled, shielded: no, Screw locking, M23, No. of pos.: 6, type of contact: Socket, Solder connection, cable diameter range: 6 mm ... 10 mm



Key Commercial Data

Packing unit	8 pc		
GTIN	4 046356 199018		
GTIN	4046356199018		

Technical data

Data of the insulating body

Coding	N
Insertion/withdrawal cycles mechanical	50
Contact connection method	Solder connection
Type of contacts	Socket
Application	Signal
Number of positions	6
Contact diameter of power contacts	2 mm
Litz wire cross section of power contacts min.	0.08 mm ²
Litz wire cross section of power contacts max.	2.5 mm ²
Nominal current per power contact at 25°C	20 A
Nominal voltage, power contact	300 V
Rated surge voltage	2.5 kV
Overvoltage category	11
Degree of pollution	3
Overvoltage category	П
Degree of pollution	3

Housing data

Note	Order information: Order contact inserts and cable clamping separately		
Housing material	Metal		
Type of locking	Screw locking		
Degree of protection (when plugged in)	IP65		
	IP67		



RC-06S1N12Z500 - 1593993

Technical data

Housing data

Thread type	M23
Cable seal data	

Cable diameter	6 mm 10 mm
	L.

Environmental Product Compliance

	Lead 7439-92-1		
China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

Approvals

Approvals

Ex Approvals			
EAC			
Approvals			

Approval details

EAC **ER** B.01742

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com