٢	T	۵	п		т		0
4	R 22.6 Max	NV Thread		S	ØA		
			Keying Sł	nown as example			
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 -Shell Material : Aluminium -Shell Plating : Black Zinc -Insulator : Thermopla -Contacts : Copper All -Seals & Grommet : Silicon Elas -Contact Plating : Gold over	n Nickel Istic Oy	m	Connecto Dim A B R R S W VV THREAD	r dimension Nominal 38.1±0.3 23.82+0.1/-0.15 32.5Max 34.9±0.4 2.2+0.9/-0.1 M18x1-6g		SOURIAU sh due to a the Specificati (profe
	-Durability : 500 Mating -Delivered with Souriau contacts and -Temperature Range : -65°C to + -Salt Spray : 500 hours	g cycles d Accessories				A 29-09-2016 ISS DATE Designed By:	5 First Release Latest modific
<u> </u>	BASIC SERIES: SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp C SHELL SIZE : 13 PLATING : Z = Black Zinc Nic	Contact	Z 03 P	A CO	ORIE NTACT TYPE : PIN(5 CONTACT LAY	 TITLE SCALE NA SOURIAU FORMAT A3	ww

F

Н

G

D

Е

	0	O D		А		
						4
	LAYOUT SHO	OWN AS EXAMPLE				3
SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
	PN: 8[Country Juris FR D713Z03PA	diction & Col Not Listed			2
2016 E	First Release Latest modification - by Date:		CUSTOM	ER DRAWING	MOD N°	- -
Aluminium Receptacle 8D series						
-[Toler	ral linear rances: ±		/ PROJECT 859		1
٩U	U WWW.SOURIAU.COM it must not be reproc communicated without			SOURIAU st not be reproduce	d or	
		IRIAU DRG N° 713Z03PA-C	I		SHEET 1/2	
	С	В		A		

Г	۲ G	m m		C 00	
4	Contact Layout 03 1 0 3#16			Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4
ω	13-03 Ctc X Y A 2.39 1.47 B 0 -2.79 C -2.39 1.47			Dim Nominal B 24.26+0/-0.25 ØC 25.65+0.25/-0	3
N				SOURIAU shall not be liable for any non-confo due to a use of the Products which does no the Specifications issued by either of the Parties (professional recommendation, technic Country Ju FR	ot comply with s or by a third party
			A 29-09-201 ISS DATE Designed By:	PN: 8D713Z03PA <pre> 16 First Release Latest modification - by Date: </pre>	MOD N° CUSTOMER DRAWING
			TITLE SCALE	General linear Tolerances:	cacle 8D series
			NA SOURIAU FORMAT	U WWW.SOURIAU.COM SOURIAU DRG N	
	H G	F E	D A3	8D713Z03PA-0	2/2 A