



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 73.19 g ± 10%

| Connector dimension | |
|---------------------|-----------------|
| Dim | Nominal |
| A | 58.7±0.3 |
| B | 42.85+0.1/-0.15 |
| R | 32.5Max |
| S | 55.6±0.4 |
| W | 3+0.9/-0.1 |
| VV THREAD | M37x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D725W29SAL

| | | | |
|----------------|---------------------------------------|--------------------------------|---|
| A | 05-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | NA | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | A3 | | SOURIAU DRG N° 8D725W29SAL-C |
| | | | SHEET 1/2 |

| | | | | | | | | | | |
|----------------|------------------------|---|---|----|---|----|---|---|---|------------------------------------|
| BASIC SERIES: | 8D | 7 | - | 25 | W | 29 | S | A | L | Delivered W/O Contacts |
| SHELL TYPE : | Jam nut Receptacle | | | | | | | | | ORIENTATION : A |
| CONTACT TYPE : | Standard Crimp Contact | | | | | | | | | CONTACT TYPE : SOCKET(500 Matings) |
| SHELL SIZE : | 25 | | | | | | | | | CONTACT LAYOUT : 25-29 |
| PLATING : | W = Olive drab Cadmium | | | | | | | | | |

Contact Layout



| Contacts (Insert arrangement 25-29) | | | | | |
|--|--------------|--------------|---------------------|-------------|-------------|
| Contact position ID | Location | | Contact position ID | Location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +000 (0.00) | +481 (12.22) | S | -091 (2.31) | +321 (8.15) |
| B | +258 (6.55) | +406 (10.31) | T | +091 (2.31) | +321 (8.15) |
| C | +395 (10.03) | +277 (7.04) | U | +228 (5.79) | +194 (4.93) |
| D | +469 (11.91) | +109 (2.77) | V | +319 (8.10) | +000 (0.00) |
| E | -460 (11.91) | -100 (2.77) | W | -240 (6.10) | -181 (4.60) |
| F | +395 (10.03) | -277 (7.04) | X | +091 (2.31) | -290 (7.37) |
| G | +263 (6.68) | -406 (10.31) | Y | -091 (2.31) | -290 (7.37) |
| H | +091 (2.31) | -472 (11.99) | Z | -240 (6.10) | -181 (4.60) |
| J | -091 (2.31) | -472 (11.99) | a | -319 (8.10) | +000 (0.00) |
| K | -263 (6.68) | -406 (10.31) | b | -228 (5.79) | +194 (4.93) |
| L | -395 (10.03) | -277 (7.04) | c | +000 (0.00) | +161 (4.09) |
| M | -469 (11.91) | -109 (2.77) | d | +134 (3.40) | +000 (0.00) |
| N | -469 (11.91) | +109 (2.77) | e | +000 (0.00) | -130 (3.30) |
| P | -395 (10.03) | +277 (7.04) | f | -134 (3.40) | +000 (0.00) |
| R | -258 (6.55) | +406 (10.31) | --- | --- | --- |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 25 | -29 | 29 | 16 | I | All | MS20057-29 |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



| Dim | Nominal |
|-----|---------------|
| B | 43.43+0/-0.25 |
| ØC | 44.7+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D725W29SAL

| | | | |
|----------------|-------------------------------------|----------------------------|---|
| A | 05-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D725W29SAL-C | | SHEET 2/2 |