


1. Wiring Diagram.



2. Cable test condition :
 Open / Short : 100%
 Insulation resistance : 5M ohms
 Contact resistance : 2 ohm
 Hipot : DC 300V / 1 sec
 3. Each pcs with PE polybag

6	CORE	RH14.2*28.5*6.35mm	2	
5	CONN	USB3.0 B MALE G/F BLUE	1	P2
4	PVC	45P PVC BLACK OVERMOLD	25g	
3	PE	LLDPE 500026 6201	16g	
2	CONN	USB3.0 A/M G/F BLUE	1	P1
1	CABLE	《28AWG (7/0.12TC) *1P+D(7/0.10TC)+AL+M》*2+28AWG (7/0.12TC) *1P+24AWG(7/0.2TC)*2C+A+D+B (96/0.12AM) OD5.5 BLACK	1	1000mm
NO.	PART NO.	DESCRIPTION	QTY	UNIT/REF
		BILL OF MATERIAL		

A	2015/05	INITIAL RELEASE	2015/11/24
REV	ECN#	DESCRIPTION	DATE
Cnc Tech, LLC		TITLE	DATE
DRAWN EDWIN/AH		DWN NO.	REV
CHECKED WENC		CUSTOMER P/N:	REV
DATE 11/24/15		CUSTOMER:	
APPROVAL		SHEET 1 OF 1	