

## ATGBICS 331-5308-C network transceiver module Fiber optic 1000 Mbit/s SFP 850 nm

**Brand :** ATGBICS **Product code:** 331-5308-C

Product name: 331-5308-C



Dell Compatible Transceiver SFP 1000Base-SX 850nm MMF 550m

ATGBICS 331-5308-C network transceiver module Fiber optic 1000 Mbit/s SFP 850 nm:

ATGBICS 331-5308 1000Base-SX supports a distance of up to 550m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. It is a hot-swappable input/output device that plugs into a Gigabit Ethernet port/slot, linking the port with the fibre-optic network. Our product is built to the exact specification of Dell 331-5308= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Df		Fastonia	
Performance		Features	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 1000 Mbit/s  Interface type * SFP  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector  SFP transceiver standard  Maximum transfer distance  Wavelength  Ethernet LAN  Ethernet interface type  Digital Diagnostics Monitoring (DDM)  Wavelength-division multiplexing (WDM)  Features  Product colour  Fiber optic  SFP  SFP  SFP  SFP  SA  A  SA  SA  Maximum transfer distance  Fast  Fast Ethernet  V  Silver	1000 Mbit/s SFP  X	Country of origin	United Kingdom
		Brand compatibility	Dell
		Power	
		Input voltage	3.3 V
		Maximum voltage	3.5 V
		Power consumption (typical)	0.8 W
	<del>-</del>	Operational conditions	
	850 nm  Fast Ethernet  X	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth	70 °C 0 - 70 °C -40 - 85 °C 5 - 95% 5 - 95% 13.4 mm 56.5 mm
Housing material	Metal ✓	Height Weight	15 g
Plug and Play Hot-Plug support		Packaging data	
5 11	4		1 nc/c)
Hot-swap Easy to install	4	Number of products included Package type	1 pc(s) Box
Lasy to Histali	4	3 71	DOX
		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.