



Click [here](#) for the 3D model.

| Dimensions |                      |
|------------|----------------------|
| L          | 3.81mm MAX           |
| H          | 5.97mm MAX           |
| T          | 3.81mm MAX           |
| S          | 5.08mm +/-0.78mm     |
| H0         | 16mm +/-0.5mm        |
| F          | 0.51mm +0.1/-0.025mm |

| Packaging Specifications |            |
|--------------------------|------------|
| Packaging                | T&R, 305mm |
| Packaging Quantity       | 2500       |

| General Information |                              |
|---------------------|------------------------------|
| Series              | GoldMax 300 Comm X7R HV      |
| Style               | Radial                       |
| Description         | GoldMax, Commercial Standard |
| RoHS                | Yes                          |
| Termination         | Tin                          |
| Failure Rate        | N/A                          |
| AEC-Q200            | No                           |
| Halogen Free        | Yes                          |

| Specifications   |  |
|--|--|
| Capacitance  | 1000 pF  |
| Measurement Condition  | 1 kHz 1.0Vrms                                      |
| Capacitance Tolerance  | 10%  |
| Voltage DC   | 1000 VDC   |
| Dielectric Withstanding Voltage                                    | 1200 VDC   |
| Temperature Range  | -55/+125°C   |
| Temperature Coefficient  | X7R  |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 0.15, 1kHz 1.0Vrms                                 |
| Dissipation Factor   | 2.5% 1kHz 1.0Vrms                                  |
| Aging Rate   | 3% Loss/Decade Hour:<br>Referee Time is 1000 Hours |
| Insulation Resistance  | 100 GOhms  |