


Ha-Vis EtherRail 4xAWG22/19 CAT5 10m



Part number	09 45 600 0188
Specification	Ha-Vis EtherRail 4xAWG22/19 CAT5 10m
HARTING eCatalogue	https://b2b.harting.com/09456000188

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Copper cable (round)
Description of the cable	for railway applications

Version

Cable length	10 m
Number of cores	4
Core structure	4x AWG 22/19

Technical characteristics

Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +90 °C
Cable diameter	7.2 7.6 mm
Minimum bending radius	6x Cable diameter
Test voltage U _{r.m.s.}	2 kV Wire / wire / shielding
Coupling attenuation @ 20 °C / 100 MHz	8 mΩ/m
Conductor resistance @ 20 °C	≤54.4 Ω/km
Insulation resistance @ 20 °C	≥5,000 MΩ x km
Signal run time @ 20 °C	≤4.4 ns/m



Technical characteristics

Impedance @ 100 MHz	100 Ω ±5 %
---------------------	------------

Material properties

Material (cable)	Polyolefin copolymer electron beam crosslinked Comp 752
Colour (cable)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

	EN 45545-2 (HL 1-3) fire protection in railway vehicles EN 50264-1 fire protection in railway vehicles EN 50306-1 fire protection in railway vehicles NFPA 130 fire protection in railway vehicles
Specifications	UN/ECE-R 118 fire protection for rolling stock EN 50306-4 Resistance to ozone EN 60811-504 High low temperature resistance EN 60811-404 High oil resistance EN 60811-404 High fuel resistance
	EN 60811-404 Alkali resistance EN 60811-404 Acid resistance DIN 51900 Low fire load EN 50618 UV resistant

Commercial data

Packaging size	1
Net weight	812 g
Net weight	75 g/m
Country of origin	Germany
European customs tariff number	85444290
eCl@ss	27061801 Data and communication cable (copper)