	10	9	8	7	6	5	4	3	2	1	
F			- ^{1.13} [28.7] REF. 1		2.83 [71.9 REF.	9] 7/8"-16UN		1			F
Е	2 1.99 [50.5] REF. 7/8"-16UN 0.18 [4.6] 2 PLACES									E	
D		<i>T/8"-16UN</i> <i>T/8"-16UN</i> <i>T/8"-16UN</i> <i>T/8"-16UN</i> <i>T/8"-16UN</i> <i>T/8"-16UN</i> <i>T/8"-16UN</i> <i>SCHEMATIC</i>									D
С				Ø 1.00 [25.4] REF.			1 2 .00 [25.4] REF.		$\xrightarrow{} 1 \\ 2 \\ \end{array}$		с
В	2										B
A	CONTACT MATERIAL: GOLD/NICKE LEGAR COPPER ALLOY INSERT MATERIAL: YELLOW TPE OVERMOLD MATERIAL: YELLOW TPE ASSEMBLY RATING: 600V, 10A ENVIRONMENTAL: -20°C TO 80°C IP67 WHEN MATED A BUILTY SYMBOLS UNLESS SPECIFIED) UNLESS SPECIFIED) UNLESS SPECIFIED) UNLESS SPECIFIED) MINCH DRAWN BY DATE INCH MM 11/10 STEL SYMBOLS UNLESS SPECIFIED) INCH/MM INCH DRAWN BY DATE INCH MINI-CHANGE 2-POLE TEE INCH INCH INCH INCH INCH INCH INCH INCH INCH INCH INCH										A
	10	9	8	7	6	5	4	3	2	1	\backslash