

## Specification Sheet

Part Number: 156-00070



Heavy Duty Cable Tie/Fir Tree Mount, 15" x .5", .04"—.26" Panel Thick, PA66HIRHSUV, Black, 100/pkg

Article Number	156-00070
Type	WSRFT9A
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>•Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.</li><li>•Fir tree provides low insertion effort yet demonstrates high extraction resistance.</li><li>•Disc feature prevents rattling in high-vibration applications and protects against debris ingress.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

<b>Short Description</b>	Heavy Duty Cable Tie/Fir Tree Mount, 15" x .5", .04"-.26" Panel Thick, PA66HIRHSUV, Black, 100/pkg
<b>Global Part Name</b>	WSRFT9A-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	120.0
<b>Minimum Tensile Strength (Metric)</b>	535
<b>Length L (Imperial)</b>	15.0
<b>Length L (Metric)</b>	380.0
<b>Fixation Method</b>	Fir Tree
<b>Identification Plate Position</b>	none
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.7
<b>Bundle Diameter Max (Imperial)</b>	4.1
<b>Bundle Diameter Max (Metric)</b>	105.0
<b>Height H (Imperial)</b>	.75
<b>Height H (Metric)</b>	19.10

<b>Panel Thickness Min(Imperial)</b>	0.039
<b>Panel Thickness Max(Imperial)</b>	0.256
<b>Panel Thickness Min (Metric)</b>	1.0
<b>Panel Thickness Max (Metric)</b>	6.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.34 - 0.36
<b>Mounting Hole Diameter D (Metric)</b>	8.7 - 9.2 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.34
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.36
<b>Mounting Hole Diameter D Max (Metric)</b>	9.25
<b>Disc Diameter(Metric)</b>	21.6
<b>Disc Diameter (Imperial)</b>	0.85
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

100

**Customs Number**

3926909988