

## Specification Sheet

Part Number: 170-03071



Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel

<b>Article Number</b>	170-03071
<b>Type</b>	BSPFR188
<b>Color</b>	Gray (GY)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.</li><li>• Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.</li></ul>
<b>Quantity Per</b>	reel

### Product Description

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description**

Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel

**Global Part Name**

BSPFR188-PET-GY

**Length L (Imperial)**

225.0

**Length L (Metric)**

68.6

**Bundle Diameter Min (Imperial)**

0.094

**Bundle Diameter Min (Metric)**

2.4

**Bundle Diameter Max (Imperial)**

0.25

**Bundle Diameter Max (Metric)**

6.4

**Diameter D (imperial)**

0.13

**Diameter D (metric)**

3.2

**Nominal Diameter (Imperial)**

1/8

**Nominal Diameter (Metric)**

3.2

**Material**

Polyester (PET)

**Material Shortcut**

PET

**Flammability**

FAR 25 UL VW-1 Mil-202 FMVSS 302

**Halogen free** Yes

**Operating Temperature (Metric)** -94°F to +257°F (-70°C to +125°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL 94 VW-1

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 225

**Package Quantity (Metric)** 68.58

**Customs Number** 5808100000

**Weight (Metric)** 0.18

**Weight (Imperial)** 0.4