## **BGA Heat Sink - High Performance** maxiFLOW w/Thermal Tape





ATS Part#: ATS-52400B-C1-R0

Description: 40.00 x 40.00 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal

Tape

Heat Sink Type: maxiFLOW
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-52400B-C2-R0

\*Image above is for illustration purpose only.

## **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

## **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.5 °C/W	3.4 °C/W	2.9 °C/W	2.6 °C/W	2.3 °C/W	2.2 °C/W	2 °C/W
	Ducted Flow	3.2	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish			
	40.00 mm	40.00 mm	7.50 mm	56.52 mm	T412	BLUE-ANODIZED			
B A	<ul> <li>Dimension A and B refer to component size.</li> <li>Dimension C is the heat sink height from the bottom of the base to the top of the fin field.</li> <li>ATS-52400B-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint-Gobain C675).</li> <li>Thermal performance data are provided for reference only. Actual performance may vary by application.</li> <li>ATS reserves the right to update or change its products without notice to improve the design or performance.</li> <li>ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.</li> <li>Contact ATS to learn about custom options available.</li> </ul>								
*Image above is for illustration purpose only.									



