

# PCS.01.250.DLLE24

### **SUMMARY**

# Wires

Coax 1



Image is for illustrative purpose only

Series 01

Termination type Female solder

IP rating 50

AWG wire size 0.00 - 0.00

Cable Ø 0.00 - 0.00 mm

**Status** active

Matching parts FFS.01.250.DLAE24

#### **Download**

Request a quote

Catalog

### **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model PCS\*: Free receptacle with cable crimping

Keying Circular, female

Housing Material Brass (gold plated [ISO 27874]) shell, collet nut, brass latch sleeve and mid pieces

Weight 1.26 g

**Performance** 

Configuration 01.250 : 1 Coax (50 Ohm)

Insulator


**Rated Current** 

#### **Others**

Endurance (Shell): 1000 mating cycles

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **DRAWINGS**





#### **Dimensions**

	А	L	<b>S</b> 1	S2
mm.	5	18	4	4
in.	0,20	0,71	0,16	0,16

## **RECOMMENDED BY LEMO**

**Tools** 

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.