

USB 3.0 SuperSpeed Extension Cable - USB-A to USB-A, M/F, Blue, 16 ft. (4.88 m)

MODEL NUMBER: U324-016





Extension cord connects two devices with USB-A connectors or extends your existing USB cable by 16 feet.

Features

16-Foot Extension Cable Connects Computers, Printers, Modems and Other USB EquipmentThis USB 3.0 SuperSpeed Type-A Extension Cable (M/F) attaches to your current USB 3.0 cable to extend it by 16-ft. (4.88 m) It connects your computer, laptop or other compatible USB 3.0 device, such as a Chromebook or Surface Pro tablet, to a USB-A keyboard, printer, portable hard drive, patch panel or other peripheral. The 16-ft. (4.88 m) length allows you great flexibility in placing equipment with respect to the power outlet.

Transfers Data at SuperSpeed Transfer Rates up to 5 GbpsThe U324-016 supports USB 3.0 speeds up to 5 Gbps—10 times the speed of USB 2.0—and better power efficiency with no device polling and lower active and idle power requirements. The cable's bi-directional data interface allows data to flow both directions simultaneously, increasing theoretical bandwidth by 10 times. Sync-N-Go technology allows the cable to quickly detect and sync the connected devices. The cable is backward compatible with previous USB generations, allowing you to use it with legacy devices.

Highlights

- Recommended for connecting computers, hard drives and other USB-A devices
- Supports USB 3.0 SuperSpeed data transfer rates up to 5 Gbps—10x faster than USB 2.0
- Bi-directional data interface allows data to flow both directions simultaneously
- 16-ft. (4.88 m) length allows great flexibility in placing devices in relationship to AC outlet
- Ideal replacement for worn-out or missing 16-ft. (4.88 m) extension cord

Applications

- Connect devices like computers, servers and external hard drives in your data center, workspace or home theater
- Extend an existing USB connection up to 16-ft. (4.88 m) to more easily place a device
- Provide a high-quality replacement for a worn-out or missing power cord

System Requirements

 Devices and cable with USB-A connectors (USB 3.0 capability required to reach USB 3.0 speeds)

Package Includes

 U324-016 USB 3.0 SuperSpeed Extension Cable, A to A, M/F, Blue, 16-ft. (4.88 m)

Specifications

OVERVIEW	
UPC Code	037332241467
Technology	USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1)
INPUT	
Product Length (in.)	192
Product Length (cm.)	487.68





Product Length (ft.) Product Length (m.) PHYSICAL Color Blue Cable Jacket Rating VW-1 Cable Outer Diameter (OD) Cable Length (ft.) Cable Length (in.) Material of Construction PVC Cable Length (cm) Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Side A - Connector 1 USB 3.0 A (MALE)	
PHYSICAL Color Blue Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 5.5MM Cable Length (ft.) 16 Cable Length (in.) 192 Material of Construction PVC Cable Length (cm) 487.68 Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Weight (kg) 0.20 Shipping Weight (lbs.) 0.43 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32 to 113 F (0 to 45 to 45 to 45 to 45 to 90% RH, No Storage Humidity Range 5% to 90% RH, No CONNECTIONS	
Color Cable Jacket Rating VW-1 Cable Outer Diameter (OD) Cable Length (ft.) Cable Length (m) Cable Length (in.) Material of Construction PVC Cable Length (cm) A87.68 Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Tone As to 158 F (-40 to 00 power of the p	
Cable Jacket Rating Cable Outer Diameter (OD) 5.5MM Cable Length (ft.) Cable Length (m) 4.87 Cable Length (in.) Material of Construction PVC Cable Length (cm) Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32 to 113 F (0 to 48 to 158 F (-40 to 0 to 90% RH, No connections) Storage Humidity Range 5% to 90% RH, No connections	
Cable Outer Diameter (OD) Cable Length (ft.) Cable Length (m) Cable Length (in.) Material of Construction Cable Length (cm) Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range CONNECTIONS	
Cable Length (ft.) Cable Length (m) 4.87 Cable Length (in.) Material of Construction PVC Cable Length (cm) Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Tonne Temperature Range 10% to 85% RH, No. CONNECTIONS	
Cable Length (m) Cable Length (in.) Material of Construction PVC Cable Length (cm) Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Tonne Connections 487.68 9.00 x 7.00 x 0.50 9.02 9.043 9.043 Polybag ENVIRONMENTAL Operating Temperature Range 100 to 45 107 108 to 85% RH, No.	
Cable Length (in.) Material of Construction PVC Cable Length (cm) Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Tone Storage Humidity Range CONNECTIONS	
Material of Construction PVC Cable Length (cm) 487.68 Shipping Dimensions (hwd / in.) 9.00 x 7.00 x 0.50 Shipping Weight (kg) 0.20 Shipping Weight (lbs.) 0.43 Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32 to 113 F (0 to 48 Storage Temperature Range -43 to 158 F (-40 to 0) Operating Humidity Range 10% to 85% RH, No. Storage Humidity Range 5% to 90% RH, No. CONNECTIONS	
Cable Length (cm) Shipping Dimensions (hwd / in.) Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS 487.68 9.00 x 7.00 x 0.50 0.43 Polybag 20 to 113 F (0 to 45) 10 to 45 10 to 85% RH, No.	
Shipping Dimensions (hwd / in.) Shipping Weight (kg) O.20 Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS 9.00 x 7.00 x 0.50 0.43 10.43 Polybag Polybag 10 to 45 10 to 45 10 to 45 10 to 85% RH, No.	
Shipping Weight (kg) Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS O.20 0.43 Polybag Polybag 10 to 45 10 to 45 10 to 45 10 to 85% RH, No.	
Shipping Weight (lbs.) Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range Storage Temperature Range Operating Humidity Range Storage Humidity Range CONNECTIONS O.43 Polybag 10 to 45 10 to 45 10 to 45 10 to 85% RH, No	
Unit Packaging Type Polybag ENVIRONMENTAL Operating Temperature Range 32 to 113 F (0 to 45 storage Temperature Range -43 to 158 F (-40 to 0 operating Humidity Range 10% to 85% RH, No storage Humidity Range 5% to 90% RH, No connections	
ENVIRONMENTAL Operating Temperature Range 32 to 113 F (0 to 45 Storage Temperature Range -43 to 158 F (-40 to 0 Operating Humidity Range 10% to 85% RH, No Storage Humidity Range 5% to 90% RH, No CONNECTIONS	
Operating Temperature Range 32 to 113 F (0 to 45 Storage Temperature Range -43 to 158 F (-40 to Operating Humidity Range 10% to 85% RH, No CONNECTIONS	
Storage Temperature Range -43 to 158 F (-40 to Operating Humidity Range 10% to 85% RH, No Storage Humidity Range 5% to 90% RH, No CONNECTIONS	
Operating Humidity Range 10% to 85% RH, No Storage Humidity Range 5% to 90% RH, No CONNECTIONS	5 C)
Storage Humidity Range 5% to 90% RH, No.	70 C)
CONNECTIONS	on-Condensing
	n-Condensing
Side A - Connector 1 USB 3.0 A (MALE)	
Side B - Connector 1 USB 3.0 A (FEMAL	.E)
Connector Plating Nickel	
Contact Plating Gold	
FEATURES & SPECIFICATIONS	
USB Specification USB 3.0 (up to 5 G	bps)
STANDARDS & COMPLIANCE	
Certifications Tested to CE, FCC	
WARRANTY	, RoHS, REACH
Product Warranty Period (Worldwide) Lifetime limited war	, RoHS, REACH



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies