

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.




| ISS      | UE NUMBER |
|----------|-----------|
| ORIGINAL |           |

(1)







NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

**OPERATING TEMPERATURE:** 

.X ±0.25 .XX ±0.13 .XXX ±0.05

20A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:

5000MΩ min.


1000V AC rms

STEEL, TIN PLATED

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, 30µ" GOLD PLATED



|  |                                      |   |                                 | SW REFERENCE NO.: 629 COMBO ASSEMBLY |       |  |
|--|--------------------------------------|---|---------------------------------|--------------------------------------|-------|--|
|  |                                      |   | DRAWN: C.B                      | DATE: JAN. 01/20                     | 19    |  |
|  |                                      |   | CHECKED:                        | DATE:                                |       |  |
|  | EDAC INC                             | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND  | SCALE: (IN C.A.D. 1:1)          | SHEET 1 OF                           | 2     |  |
|  | YOUR CONNECTION TO QUALITY & SERVICE | SHALL NOT BE REPRODUCED, OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 629-2WK2640-2T6 |                                      | ISSUE |  |
|  |                                      |   | PART NUMBER: 629-2WK2640-2T6    |                                      | 1     |  |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

