


TOLERANCE UNLESS OTHERWISE SPECIFIED		
.X	±0.25	
.XX	±0.13	

.XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, 30µ" GOLD PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

40A (CURRENT) POWER/CO-AX CONTACT RATING:

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms



11.9	
20.33	

COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 629 C	629 COMBO ASSEMBLY				
DRAWN: C.B	DATE: JAN. 01/2019				
CHECKED:	DATE:				
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2				
DRAWING NUMBER: 629-36W4650-4ND					

629-36W4650-4ND

PART NUMBER:



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)

2W2





5W1

0000 3W3








11W1

⊙ ⊙ ⊙ ⊙ ⊙ ⊙ ⊙ ⊙






13W3










17W5











21W4









COMBINATION D-SUB



AND SPECIFICATIONS
TY OF EDAC INC.,AND
PRODUCED,OR COPIED
BASIS FOR THE
SALE OF APPARATUS
N PERMISSION.

OTHORIZED.

SCALE: N.T.S
DRAWING NUMBER:

DRAWN: C.B		DATE:	JAN.	01/20	19
CHECKED:		DATE:			
SCALE: N.T.S		SHEET	2	OF	2
DRAWING NUMBER:	629-36W4650-4ND			ISSUE	

629-36W4650-4ND

629 COMBO ASSEMBLY

SW REFERENCE NO.:

