## **BGA Heat Sink - High Performance** maxiFLOW w/Thermal Tape





ATS Part#: **ATS-52325G-C1-R0** 

Description: 32.50 x 32.50 x 12.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal

Tape

Heat Sink Type: maxiFLOW
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-52325G-C2-R0

\*Image above is for illustration purpose only.

## **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

## **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	3.5 °C/W	2.8 °C/W	2.4 °C/W	2.2 °C/W	2 °C/W	1.8 °C/W	1.7 °C/W
	Ducted Flow	2.8	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image Dimension A		Dimension B	Dimension C	Dimension D	TIM	Finish			
	32.50 mm	32.50 mm	12.50 mm	57.46 mm	T412	BLUE-ANODIZED			
B A	<ul> <li>Notes:</li> <li>Dimension A and B refer to component size.</li> <li>Dimension C is the heat sink height from the bottom of the base to the top of the fin field.</li> <li>ATS-52325G-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material (Saint-Gobain C675).</li> <li>Thermal performance data are provided for reference only. Actual performance may vary by application.</li> <li>ATS reserves the right to update or change its products without notice to improve the design or performance.</li> <li>ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.</li> <li>Contact ATS to learn about custom options available.</li> </ul>								
*Image above is for illustration purpose only.									



