



a YAGEO company

## C114C391J1G5CA

LDD Comm COG, Ceramic, 390 pF, 5%, 100 VDC, COG





Click here for the 3D model.

| Dimensions |                   |
|------------|-------------------|
| D          | 2.29mm +/-0.254mm |
| L          | 4.06mm +/-0.254mm |
| LL         | 38.1mm MIN        |
| F          | 0.51mm -0.08mm    |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 200       |

| General Information |   |  |
|---------------------|---|--|
| Series              | LDD Comm COG  |  |
| RoHS                | No  |  |
| Prop 65             | ▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.  |  |
| SCIP<br>Number      | f30e2214-6f19-489b-928a-4aa9281a81a7  |  |
| Termination         | Lead (SnPb)   |  |
| AEC-Q200            | No  |  |
| Notes               | Lead Length Shown Is For Parts Supplied In Bulk, See<br>Packaging Specifications For Lead Lengths When Not<br>Provided In Bulk. |  |

| Specifications                  |                |  |  |
|---------------------------------|----------------|--|--|
| Capacitance                     | 390 pF         |  |  |
| Capacitance Tolerance           | 5%             |  |  |
| Voltage DC                      | 100 VDC        |  |  |
| Dielectric Withstanding Voltage | 250 VDC        |  |  |
| Temperature Range               | -55/+125°C     |  |  |
| Temperature Coefficient         | COG            |  |  |
| Dissipation Factor              | 0.1% 1 mHz 25C |  |  |
| Insulation Resistance           | 2.564 GOhms    |  |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.