



Click [here](#) for the 3D model.

| Dimensions |                 |
|------------|-----------------|
| D          | 13mm MAX        |
| T          | 5mm MAX         |
| S          | 10mm +/-1mm     |
| LL         | 4mm +/-1mm      |
| F          | 0.55mm +/-0.1mm |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 500       |

| General Information |                           |
|---------------------|---------------------------|
| Series              | C900AC SFTY X1-440 Y2-300 |
| Style               | Radial Disc               |
| RoHS                | Yes                       |
| Termination         | Tin                       |
| Failure Rate        | N/A                       |
| Qualifications      | UL, ENEC, VDE, CSA, CAN   |
| AEC-Q200            | No                        |
| Halogen Free        | Yes                       |
| Component Weight    | 1.1 g                     |

| Specifications                  |                            |
|---------------------------------|----------------------------|
| Capacitance                     | 3900 pF                    |
| Capacitance Tolerance           | 20%                        |
| Voltage AC                      | 440 VAC (X1), 300 VAC (Y2) |
| Dielectric Withstanding Voltage | 2600 VDC                   |
| Temperature Range               | -40/+125°C                 |
| Temperature Coefficient         | Y5U                        |
| Dissipation Factor              | 2.5%                       |
| Insulation Resistance           | 10 GOhms                   |
| Safety Class                    | X1/Y2                      |