

## F873DY184K760Z

F873, Film, Metallized Polypropylene, Safety, 0.18 uF, 10%, 760 VAC (X1), 1500 VDC, 110°C, Lead Spacing = 22.5mm



Click here for the 3D model.

| Dimensions |                 |
|------------|-----------------|
| L          | 26mm -0.5mm     |
| Н          | 24.5mm -0.5mm   |
| Т          | 15.5mm -0.5mm   |
| S          | 22.5mm +/-0.4mm |
| LL         | 4mm +2mm        |
| F          | 0.8mm +/-0.05mm |
| G          | 0.5mm NOM       |

| Packaging Specifications |            |
|--------------------------|------------|
| Packaging                | Pizza, Box |
| Packaging Quantity       | 252        |

| General Information |                          |
|---------------------|--------------------------|
| Series              | F873                     |
| Dielectric          | Metallized Polypropylene |
| Style               | Radial                   |
| Features            | MKP EMI Safety           |
| RoHS                | Yes                      |
| Lead                | Cut/Short                |
| Safety Class        | X1                       |
| Qualifications      | ENEC, UL, cUL, CQC       |
| AEC-Q200            | No                       |
| THB Performance     | No                       |
| Component Weight    | 11.28 g                  |
| Miscellaneous       | ClimCat: 40/110/56/B.    |
| Shelf Life          | 104 Weeks                |

| Specifications        |              |
|-----------------------|--------------|
| Capacitance           | 0.18 uF      |
| Capacitance Tolerance | 10%          |
| Voltage AC            | 760 VAC (X1) |
| Voltage DC            | 1500 VDC     |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.1% 1kHz    |
| Insulation Resistance | 30 GOhms     |
| Max dV/dt             | 300 V/us     |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.