




UD6-3-3-F

Ruland UD6-3-3-F, 3/16" x 3/16" Double Universal Joint, Friction Bearing, Steel, 0.370" OD, 2.438" Length





Description

Ruland UD6-3-3-F is a double cardan friction bearing universal joint with 0.1875" x 0.1875" bores, 0.370" OD, and 2.438" length. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UD6-3-3-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT6/10-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Prop 65	▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Tariff Code	8483.60.4000	UNSPC	25173810
Matching Boot Cover	UBOOT6/10-NI-KIT	UPC	634529288863
Weight (lbs)	0.050000	Recommended Lubricant	LUBRIPLATE No. 1200-2
Manufacturer	Belden Universal	Country of Origin	USA
Max Operating Angle	90°	Material Specification	Alloy Steel
Peak Torque	90 in-lb	Rated Torque	18 in-lb
Yoke Length (LY)	0.875 in	Hub Depth (LH)	0.670 in
Length (L)	2.438 in	Center Yoke Length (LC)	0.688 in
Joint Outer Diameter (OD)	0.370 in	Bore Tolerance	+0.0010 in / -0.0000 in
B1 Max Shaft Penetration	0.670 in	B2 Max Shaft Penetration	0.670 in
Bore (B1)	0.1875 in	Small Bore (B2)	0.1875 in