

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	

(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED

THERMOPLASTIC POLYESTER, UL94V-0

OPERATING TEMPERATURE: -55°C ~ 125°C

POWER/CO-AX CONTACT RATING:


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 10A (CURRENT)

5000MΩ min.

1000V AC rms

				SW REFE	RENCE NO.: 629 C	OMBO ASSEMBLY	
		COMBINATION	D-SUB	DRAWN:	C.B	DATE: JAN. 01/20	19
				CHECKED	D:	DATE:	
		EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE:	(IN C.A.D. 1:1)	SHEET 1 OF	2
		TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-3W3-640-1NB			ISSUE
YC	OUR CONNECTION TO	QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUI	MBER: 629-3W3	-640-1NB	1



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

YOUR CONNECTION TO QUALITY
TOUR CONNECTION TO QUALITY

.X ±0.25 .XX ±0.13 .XXX ±0.05

