

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:

.X ±0.25 .XX ±0.13 .XXX ±0.05


POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 10A (CURRENT)


-55°C ~ 125°C

5000MΩ min.

1000V AC rms



				SW REFERENCE NO.: 629 COMBO ASSEMBLY			
			DRAWN: C.B		DATE: JAN. 01	/2019	
			CHECKED:		DATE:		
	EDAC INC	ARE THE PROPERTY OF EDAC INC.,AND , ONTARIO ADA OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	SCALE: (IN C.A.D. 1	:1)	SHEET 1 ()F 2	
	TORONTO, ONTARIO CANADA		DRAWING NUMBER:	629-7W2-	-250-1T3	ISSUE	Ξ
YOUR CONNECTION TO	QUALITY & SERVICE		PART NUMBER:	629-7W2-	-250-1T3	1	



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

ED	AC	EDAC II TORONTO, C CANAE
YOUR CO	NNECTION T	O QUALITY & SE

