

Note: This datasheet may be out of date. Please download the latest datasheet of GRM033R71C101KA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM033R71C101KA01%23

GRM033R71C101KA01J "#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > GRM033R71C101KA01D GRM033R71C101KA01W

Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment,Industrial
	Equipment, Mobile Electronics, Medical
	equipment [GHTF A/B/C] except for
	implant equipment,Automotive
	infotainment/comfort equipment
	Please refer to Our Website and
	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.

GRM033R71C101KA01J



PackagingSpecificationsStandard
Packing
QuantityDφ180mm Reel Paper Tape15000Wφ180mm Reel W8P1 Paper
Tape30000Jφ330mm Reel Paper Tape50000

Mass (typ.)	
1 piece	0.33mg



Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRM033R71C101KA01J

Note: This datasheet may be out of date. Please download the latest datasheet of GRM033R71C101KA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM033R71C101KA01%23

"#" indicates a package specification code.



Specifications

Length	0.6±0.03mm
Width	0.3±0.03mm
Thickness	0.3±0.03mm
Capacitance	100pF ±10%
Distance between external terminals g	0.2mm min.
External terminal size e	0.1 to 0.2mm
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	16Vdc
Size code in inch(mm)	0201 (0603M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55℃ to 125℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

