ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INFORMATION AND ADDRESS INDUSTRIES®	PC, Bannock	burn, Illinois. A	ll rights reserved un tions.	nder both	This docum level parts, t	ent is a declar the declaration	ration of the n encompass	substances ses all lowe	within the ma r level materia	nufacturer list ds for which t	ed item. he manut	Note: if th facturer ha	e item is an ass s engineering r	sembly with lower responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Information															
Company name*			Company unique ID			Unique ID Authority					Response Date*				
onsemi									2023	2023-06-08					
Contact Name Title - Contact			et	P			Phone - Contact*				Email - Contact*				
Product-Env-Stewards Pr			Product Enviro Compliance			NA				Pro	Product-Env-Stewards@onsemi.com				
Authorized Representative* Ti			Title - Representative			Phone - Representative*				Ema	Email - Representative*				
Product-Env-Stewards	Product Enviro Compliance				NA				Pro	Product-Env-Stewards@onsemi.com					
Requester Item Number	Mfr Iter	n Number	Mfr Item Name			Effective Da	ate Version	n İ	Manufacturing Site		Weig	ht*	UOM	Unit Type	
	NCP176	NCP176AMX300TCG LDO 3.0V		3.0V Active Discharge		2023-06-08		-	MY1		1.81		mg	Each	
Manufacturing Proccess Informa	tion					1	ł								
Terminal Plating / Grid Array M	aterial	Terminal Base Alloy		-STD-020 MS	D-020 MSL Rating		Peak Process Body Ten		erature Max Time at Peak T		Temperature Number of Reflow		of Reflow Cyc	les	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		CU Alloy 1				260		C	C 30		seconds 3				
Comments															
evel 1 - maximum time at peak temperat	ure during so	dering is 10-3	0 seconds												
or more information regarding material	composition	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth						
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	stislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.09	mg	Supplier	Silicon (Si)	7440-21-3		0.09	mg	
Die Attach	0.04	mg	Supplier	Silver (Ag)	7440-22-4		0.03	mg	
			Supplier	Epoxy resins	129915-35-1		0.01	mg	
Lead Frame	0.78	mg	Supplier	Tin (Sn)	7440-31-5		0.0019	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0017	mg	
			Supplier	Chromium (Cr)	7440-47-3		0.0019	mg	
			Supplier	Copper (Cu)	7440-50-8		0.7744	mg	
Mold Compound-Black	0.87	mg		Epoxy Phenol Resin	proprietary data		0.0913	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		0.7786	mg	
Plating	0.01	mg	Supplier	Palladium (Pd)	7440-05-3		0.0005	mg	
			В	Nickel (Ni)	7440-02-0		0.009	mg	
			Supplier	Gold (Au)	7440-57-5		0.0005	mg	
Wire Bond	0.02	mg	Supplier	Palladium (Pd)	7440-05-3		0.0002	mg	
			Supplier	Copper (Cu)	7440-50-8		0.0198	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).