


10-Port USB Hub with Power Supply and International Plug Adapters

MODEL NUMBER: U223-010-INT



Adds 10 USB-A ports to your laptop or computer for connecting printers, hard drives, keyboard/mice and other USB peripherals.

Features

USB 2.0 Hub Adds up to 10 USB Devices to Your Computer or Laptop

This USB hub with a sturdy plastic housing connects 10 USB devices, such as external hard drives, printers, keyboards/mice, MP3 players and barcode scanners, to your PC, laptop or other device with a USB-A port. The hub supports USB 2.0 data transfer rates up to 480 Mbps and is backward compatible with USB 1.1 devices. It provides easy-to-access USB ports to computers stored in cabinets, behind furniture or other hard-to-reach locations.

Plug-and-Play Hub Is Convenient to Use All Over the World

The U223-010-INT requires no software to download and install. It connects to a host computer with the included USB-A to USB-B cable and draws power through the included external power supply. A blue LED indicates the unit is receiving power. Four included international plug adapters (North America, United Kingdom, Europe and Australia) ensure you can use this hub almost anywhere.

Highlights

- Supports USB 2.0 speeds up to 480 Mbps to ensure reliable data transfers
- International plug adapters allow connection to AC power all over the world
- Blue LED indicates the hub is receiving power from the included supply
- Compatible with most recent Windows and macOS versions
- Plug-and-play operation with no software required for easy, immediate installation

System Requirements

Compatible with Windows 98SE, Vista, XP, Me, Win2000, 7, 8, 10 and 11; Mac OS X 10.8 Mountain Lion and macOS Big Sur

Package Includes

- U223-010-INT 10-Port USB 2.0 Hub
- USB Mini-B to USB-A cable (M/M)
- External power supply (Input: 100–240V, 50/60 Hz, 1.5A; Output: 5V 4A)
- (4) International plug adapters (North America, U.K., Europe, Australia)

Specifications

OVERVIEW	
UPC Code	037332269713
Product Type	Hub
Technology	USB 2.0 (High Speed)
Host Connector	USB A (MALE)
VIDEO	
Number of Monitors Supported	0
Video Ports	USB A (MALE)

DATA	
Data Ports	(10) USB A (FEMALE)
NETWORK	
Network Ports	USB A (FEMALE)
INPUT	
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Input Plug Type	AS/NZS 3112; BS1363; NEMA 1-15P; Schuko
Input Plug Type Details	See POWER: AC Power Adapter specifications
Bus Powered	No
POWER	
Power Source Type	AC Adapter
External Power Supply Plug(s)	AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 1.5A
External Power Supply Output Specs (V / A)	5V / 4A
External Power Supply Cord Length (ft.)	5
External Power Supply Cord Length (m.)	1.5
AC Adapter	Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A, 5 ft.
DC Barrel Plug	OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Blue (Power)
PHYSICAL	
Color	Black
Material of Construction	ABS
Unit Dimensions (hwd / in.)	8.712 x 1.311 x 0.629
Unit Dimensions (hwd / cm)	22.21 x 3.33 x 1.6
Unit Packaging Type	Box
Unit Weight (lbs.)	0.189
Unit Weight (kg)	0.09
ENVIRONMENTAL	

Operating Temperature Range	32 to 113 F (0 to 45 C)
Storage Temperature Range	14 to 176 F (-10 to 80 C)
Operating Humidity Range	10 to 85% RH, Non-Condensing
Storage Humidity Range	5 to 90% RH, Non-Condensing
Power Provided to Connected Device(s)	500mA from the USB 2.0 computer port is shared between the hub ports
CONNECTIONS	
Number of Ports	10
Side A - Connector 1	USB MINI-B 5-PIN (FEMALE)
Side B - Connector 1	(10) USB A (FEMALE)
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
USB Specification	USB 2.0 (up to 480 Mbps)
Driver Required	No
STANDARDS & COMPLIANCE	
External Power Supply Certifications	BSMI; C-Tick; CCC; CE; DOE; GS; RoHS; TUV; UL; WEEE
Product Certifications	NOM (Mexico)
Product Compliance	RoHS; CE (Europe); REACH; WEEE; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty