

10.70	 		
5.80		_	
9.4	0		
2.5	4		_
			 -


.XX ±0.13

.XXX ±0.05

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	20A (CURRENT)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC WITHSTANDING VOLTAGE:	1000V AC rms

	SW REFERENCE NO.: 630 COMBO ASSEMBLY				
COMBINATION	DRAWN: C.B	DATE: JAN. 01/2019			
		CHECKED:	DATE:		
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
EDAC INC TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-7W2	-240-2T1	ISSUE	
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-7W2	-240-2T1	1	



HS F COMPLIANT

