	רד Q ב		7			
4	Z PEQUIT PEQUIT PEQUIT		4			
ω		LAYOUT SHOWN AS EXAMPLE	3			
	Keying Shown as example					
	CHARACTERISTICS   Connector dimension     -Standard : Based on MIL-DTL-38999 Series III   Dim   Nominal					
2	-Shell Material   : Aluminium     -Shell Material   : Aluminium     -Shell Plating   : Black Zinc Nickel     -Insulator   : Thermoplastic     -Contacts   : Copper Alloy     -Seals & Grommet   : Silicon Elastomer					
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	PN: 8D517Z22BN       A     18-10-2016       First Release				
	-Temperature Range65°C to +175°C					
	-Salt Spray : 500 hours	ISS DATE Latest modification - by MOD N°				
Designed By: Date: CUSTOR   TITLE Aluminium Plug 8D serie						
_	BASIC SERIES: 8D 5 - 17 Z 22 B N SHELL TYPE : Plug with RFI Shielding	SCALE General linear NPRDS / PROJECT   NA ± 859	-			
	CONTACT TYPE : Standard Crimp Contact   SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Ma					
	PLATING : Z = Black Zinc Nickel CONTACT LAYOUT :	T : 17-22 FORMAT SOURIAU DRG N° SHEET	_			
•		A3 8D517Z22BN-C 1/2				

	Ŧ	۵	г П	т		0
4		Contact Layout 22				
	Cto	2#12 2#8 Triax 17-22 X Y				
۵	Ctc A B C D	X     Y       0     4.57       6.32     0       0     -4.57       -6.32     0				
	-					SOURIAU shall not be liable for a due to a use of the Products v
0						the Specifications issued by either (professional recommend Coun FR
					A 18-10-20	PN: 8D517
					ISS DATE Designed By: TITLE	Latest modification - by Date: Alumi
<b>_</b>					SCALE	General linear Tolerances: ±
					FORMAT A3	U WWW.SOURIAU. SOURIAU 8D517Z
l	Н	G	F	E	D	C

