



Product: <u>5306UE</u> ☑

Security & Sound, #18-8c, BC, CMR

Product Description

Security & Sound Cable, Riser-CMR, 8-18 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

Product O	verview					
Suitable Applications:			Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls			
Constructi	on Details					
Conductor						
Element	Number of Element	Size	Stranding	Material		
Conductor(s)	8	18 AWG	7x26	BC - Bare Copper		
Insulation						

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PO - Polyolefin	0.009 in (0.23 mm)	0.062 in (1.6 mm)	Black, Red, White, Green, Brown, Blue, Orange, Yellow

Outer Jacket

	Material	Nom. Thicknes	s Nom. Diameter	Ripcord
F	PVC - Polyvinyl Chloride	0.018 in (0.46 mi	m) 0.241 in (6.12 mm)	Yes
Overall Cable Diameter (Nominal):		Nominal): 0.	241 in (6.12 mm)	

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Conductor(s)	6.5 Ohm/1000ft	21.5 pF/ft (70.5 pF/m)	9.8 Amps per conductor @ 25°C

Voltage



Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-20°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
2 4 in (61 mm)	2.4 in (61 mm)
.4 111 (0 1 111111)	2.4 111 (01 111111)
Max. Pull Tension	n:
Bulk Cable Weig	ht:

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor	
Flammability / Reaction to Fire:	UL 1666 Riser, IEEE 1202 FT4	
NEC / UL Compliance:	Article 800, CMR	
CEC / C(UL) Compliance:	CMG	
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Plenum Number:	6306UE	

History

Update and Revision:	Revision Number: 0.429 Revision Date: 01-20-2023

Part Numbers

Variants

Item #	Color	UPC
5306UE 0081000	Gray	612825159995
5306UE 008500	Gray	612825336945

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.