

# TXIWKT

## HDMI 2.0b (18Gbps) In Wall

### TX and RX Kit



The TXIWKT is a HDMI 2.0b (18Gbps) / USB-C In-wall Decora® style transmitter coupled with a small receiver (about credit card sized footprint) that provides the power to the TX. There is a USB-C input, USB-C charge port, and an HDMI Type-A input with an input source button to choose between the two types of inputs. The transmission technology is a low heat digital format.

## Features:

- HDMI 2.0b (18Gbps)
- USB-C / HDMI Type-A inputs
- Single power supply (RX end)
- LED Indicators for Input, Power, & Link
- 35m/50m [4K@60hz./4K@30Hz.]
- Wall Plate trim included
- USB-C Charge port
- Single space Decora® design
- Compact RX device (Credit card sized footprint)
- Low heat encoding technology
- 3-Year Warranty

# SIMPLIFIED

MFG

## Specifications:

Technical	
<b>HDMI Compliance</b>	HDMI 2.0b Type –A input
<b>USB Compliance</b>	USB Type-C Input
<b>HDCP Compliance</b>	HDCP 2.2 and HDCP 1.4
<b>Video Bandwidth</b>	18 Gbps
<b>Video Resolutions</b>	up to 4K2K@50/60Hz (YUV4:4:4), 4K2K@30Hz, 1080P@120Hz, and 1080P 3D@60Hz
<b>Color Space</b>	RGB, YCbCr 4:4:4, YCbCr 4:2:2
<b>Color Depth</b>	10-bit, 12-bit
<b>HDMI Audio Formats (Pass-through)</b>	LPCM 2/5.1/7.1CH, Dolby Digital, DTS 5.1, Dolby Digital+, Dolby TrueHD, DTS-HD Master Audio, Dolby Atmos, DTS:X
<b>ESD Protection</b>	Human body model — ±8kV (air-gap discharge) & ±4kV (contact discharge)
Connections	
<b>Inputs</b>	TX: 1x HDMI Type A [19-pin female] 2x USB-C INPUT 1x Service [Mini-USB jack] RX: 1x RJ45 Input 1 Power connection [12V] 1x Service [Mini-USB jack]
<b>Outputs</b>	TX: 1x RJ45 Output RX: 1x HDMI Type A [19-pin female]
Mechanical	
<b>Housing</b>	Metal Enclosure
<b>Color</b>	TX White, RX Black
<b>Dimensions [RX]</b>	88mm [W] x 61mm [D] x 18mm [H] 3.5"x2.4"x0.67"
<b>Dimensions [TX]</b>	68mm [H] x 60mm [D] x 33mm [W] 2.75"x2.5"x 1.5"
<b>Weight RX/TX</b>	144g (5.125oz) / 205g (7.25oz)
<b>Power Supply</b>	Input: AC100 - 240V 50/60Hz Output: DC 12V/1A (US/EU standards, CE/FCC/UL certified)
<b>Power Consumption</b>	3.84W (Max)
<b>Operation Temperature</b>	32 - 104°F / 0 - 40°C
<b>Storage Temperature</b>	-4 - 140°F / -20 - 60°C
<b>Relative Humidity</b>	20 - 90% RH (no condensation)