

## Tool - UNIFOX-CE VDE\_DB - 1212817

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Combination pliers, angled design, with opening spring and locking device, cross-notched gripping surface, integrated M8 ... M10 ring wrench, VDE 1000 V AC/1500 V DC tested, type of packaging: with holder for sales display (backcard)

### Your advantages

- Ergonomic handle design to eliminate fatigue when working
- Excellent transformation ratios for excellent gripping and cutting performance
- Noticeably less force required on the part of the user
- UNIFOX ... VDE-insulated combination pliers in straight and angled versions

### Key Commercial Data

Packing unit	6 pc
GTIN	
GTIN	4046356994828

### Technical data

#### Dimensions

Length (b)	200 mm
------------	--------

#### General

Color	black
Test standard	DIN EN 60900 (VDE 0682 PART 201)
	DIN ISO 5745

#### Standards and Regulations

Test standard	DIN EN 60900 (VDE 0682 PART 201)
	DIN ISO 5745

#### Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration
---------------------------	---

### Approvals

Approvals

# Tool - UNIFOX-CE VDE\_DB - 1212817

## Approvals

---

Approvals


VDE Zeichengenehmigung / EAC

---

Ex Approvals

---

## Approval details

VDE Zeichengenehmigung		<a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a>	109845
------------------------	---	---	--------

EAC			RU x- DE.xx08.B.02974
-----	---	--	--------------------------

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>