| د. ۵ | | | LAYOUT SHOWN AS EXA | AMPLE | |
|--|------------------------------------|--------------|---|--------------------------------|----------|
| Keying Shown as example | | | | | |
| | nnector dimension | | | | |
| -Standard : Based on MIL-DTL-38999 Series III ØS | | | | | |
| -Shell Material : Aluminium Z -Shell Plating : Olive drab Cadmium VV THRE | 31 Max AD M34x1-6g | | SOURIAU shall not be liable for any n due to a use of the Products which | | |
| -Insulator : Thermoplastic | | | the Specifications issued by either of the | he Parties or by a third party | |
| -Contacts : Copper Alloy | | | (professional recommendation | n, technical notice.) | |
| -Seals & Grommet : Silicon Elastomer | | | Country | |] |
| | | [| FR | Not Listed |] |
| -Durability : 500 Mating cycles | | | PN: 8D523W0 | 06SCL | |
| -Delivered without Souriau contacts | | | | | |
| -Temperature Range - 65°C to +175°C -Salt Spray : 500 hours | | A 07-10-2016 | First Release | | |
| | | ISS DATE | Latest modification - by | | MOD N° |
| | | Designed By: | Date: | CUSTOMER DRAWING | |
| | | TITLE | Aluminiu | um Plug 8D series | |
| BASIC SERIES: 8D 5 - 23 W 06 S C L | | SCALE | General linear | NPRDS / PROJECT | |
| | Delivered W/O Contents | | Tolerances: | 859 | |
| SHELL TYPE : Plug with RFI Shielding | Delivered W/O Contacts | | | This document is the prop | perty of |
| CONTACT TYPE : Standard Crimp Contact | ORIENTATION : C | SOURIAU | WWW.SOURIAU.CO | it must not be reprodude | |
| | CONTACT TYPE : SOCKET(500 Matings) | | | communicated without pe | |
| PLATING : W = Olive drab Cadmium | CONTACT LAYOUT : 23-06 | | SOURIAU E | | SHEET |
| | 7 | A3 | 8D523W06 | 6SCL-C | 1/2 |

| | Т | ۵ | г | m | D | 0 |
|----------|----------|--|-----|---|--------------------------|---|
| | | Contact Layout | | | | |
| | | 06 | | | | |
| 4 | | | | | | |
| | | $\begin{pmatrix} & & & \\ & & & \end{pmatrix}$ | | | | |
| | | \smile | | | | |
| | | 6#8 Concentric Twinax | | | | |
| | | Service M | 7 | | | |
| | Ctc | 23-06 X Y | - | | | |
| | A | 0 9.24 | - | | | |
| | B | 8.81 2.87 | 1 | | | |
| | С | 5.43 -7.49 | | | | |
| ω | D | -5.43 -7.49 | | | | |
| | E | -8.81 2.87 | - | | | |
| | F | 0 0 | | | | |
| | | | | | | |
| | | | | | | |
| | – | | | | | COUDIALL shall not be lighte for an |
| | | | | | | SOURIAU shall not be liable for an due to a use of the Products wi |
| | | | | | | the Specifications issued by either o |
| | | | | | | (professional recommenda |
| N | | | | | | Count |
| | | | | | | PN: 8D523V |
| | | | | | | 110.003230 |
| | | | | | A 07-10-20 | 16 First Release |
| | | | | | ISS DATE Designed By: | Latest modification - by Date: |
| | | | | | Designed by. | |
| | | | | | TITLE | Alumir |
| | | | | | SCALE | General linear |
| _ | | | | | NA | t |
| | | | | | SOURIA | J WWW.SOURIAU.C |
| | | | | | FORMAT | COLIDIAL |
| | | | | | A3 | SOURIAU 8D523W |
| | Н | G | F | E | D | C |
| | | | 1 I | | | |

| | | | | 4 | | |
|--|--|---------------------------------|--------------|---|--|--|
| | | | | | | |
| | | | | 3 | | |
| any non-confor which does not r of the Parties dation, technica intry Ju R SWO6SCL | t comply wi or by a thir al notice.) risdiction & Not Li | th d party c Control List | | 2 | | |
| | CUST | OMER DRAWING | MOD N° | | | |
| ninium Plug | | | | | | |
| ır | NPRDS / PROJECT 859 | | | | | |
| .COM This document is the property of SOURIAU it must not be reproduced or communicated without permission | | | | | | |
| U DRG N V06SCL-(| | 1 | SHEET 2/2 | | | |
| В | | Α | | | | |

Þ

ω