

SUMMARY

Wires



Image is for illustrative purpose only

| | |
|------------------|-------------------------|
| Series | 2S |
| Termination type | No contacts / Accessory |
| IP rating | 0 |
| AWG wire size | 0.00 - 0.00 |
| Cable Ø | 0.00 - 0.00 mm |
| Status | active |

Download

[Request a quote](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|------------------------------|
| Shell Style/Model | GCA*: Earthing washer |
| Keying | No keying |
| Housing Material | Brass (CuSnZn plated) washer |
| Weight | .71 g |

Performance

| |
|---------------|
| Configuration |
| Insulator |
| Rated Current |


Others

| | |
|----------------------|-----------------------------|
| Temp (min / max): | -55° C / +250° C |
| Humidity (max): | <=95% [at 60 deg C / 140 F] |
| Vibration: | 15 g [10 Hz - 2000 Hz] |
| Shock Resistance: | 100 g [6 ms] |
| Climatical Category: | 50/175/21 |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)
12NC part number: 4022.438.32891

DRAWINGS



No keying

Dimensions

| | A | B | L | N |
|-----|------|------|------|------|
| mm. | 20 | 15.2 | 0.5 | 32 |
| in. | 0,79 | 0,60 | 0,02 | 1,26 |

RECOMMENDED BY LEMO

Tools

Cables

| | | | |
|--------|--|--|--|
| 121221 | | | |
| 131221 | | | |
| 151221 | | | |
| 161221 | | | |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.