
Ŧ	۵	п –	m	0







LAYOUT SHOWN AS

Keying Shown as example

## CHARACTERISTICS

BASIC SERIES:

SHELL SIZE : 19

PLATING : F = Nickel

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

ယ

 $\sim$ 

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material : Aluminium : Nickel -Shell Plating -Insulator : Thermoplastic -Contacts : Copper Alloy : Silicon Elastomer -Seals & Grommet -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories : -65°C to +200°C -Temperature Range : 48 hours -Salt Spray -Mass : 43.68 g ± 10%

8D 0

G

19

F

32

S

F

Е

Dim	Nominal
Р	3.25±0.2
PP	4.93±0.2
R1	29.36
R2	26.97
S	36.5±0.3
V	20.83+0/-1.25
W	2.1/2.5
Z	31.5 Max
VV THREAD	M28x1-6g

ORIENTATION : E

CONTACT LAYOUT : 19-32

CONTACT TYPE : SOCKET(500 Matings)

Е

SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend



Φ		Þ				
				4		
AS EXAMPLE				3		
any non-conformity or damage which does not comply with er of the Parties or by a third party adation, technical notice.)						
9F32SE				2		
			MOD N°			
um Receptac	n Receptacle 8D series					
		59		1		
J.COM	COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
U DRG N°			SHEET			
PF32SE-C		A	1/2	J		
2	1					

