<u>م</u> ت	т (Г		0	₪ >		
4						4
ω	I		LAYOUT SHOWN AS EXAI	ЛРLE		3
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	DimNominalØS25 Max					
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country FR	Jurisdiction & Control List Not Listed]	
 Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles 			L L L L L L L L L L L L L L L L L L L	Not Listed]	2
-Delivered without Souriau contacts			PN: 8D511W9	8PDL		
-Temperature Range : -65°C to +175°C		A 18-10-2016	5 First Release			\neg
-Salt Spray : 500 hours		ISS DATE	Latest modification - by		MOD N°	
		Designed By:	Date:	CUSTOMER DRAWING	NICEN	
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 11 W	98 P D L	SCALE	General linear	NPRDS / PROJECT		_
→ SHELL TYPE : Plug with RFI Shielding	Delivered W/O	Contacts NA	Tolerances:	859		
CONTACT TYPE : Standard Crimp Contact				This document is the pro SOURIAU	perty of	-
SHELL SIZE : 11	CONTACT TYPE : PIN(500		WWW.SOURIAU.CO	M it must not be reproduc communicated without pe		
PLATING : W = Olive drab Cadmium	CONTACT LAYOL		SOURIAU D		SHEET	-
		A3	8D511W98		1/2	
					-/-	

	Ŧ	۵ D	нт —	m	Ū	0	
4	-×(Contact Layout $A \oplus B \oplus $					
	Continue of the second	A + 000 (0.00) +.130 (3.30) 3 +.130 (3.30) +.000 (0.00) 2 +.065 (1.65) 113 (2.87) 0 065 (1.65) 113 (2.87) 5 +.130 (3.30) +.000 (0.00) * +.000 (0.00) +.000 (0.00) * +.000 (0.00) +.000 (0.00)					
ى س							
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional record	oducts w / either o
22						PN: 8D!	Count FR 511V
					A 18-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:	
-					SCALE NA	General General Toler	Alumir al linear rances: t
					FORMAT A3	SOU	
l	Н	G	F	E	D	C	

Φ			A		_	
					4	
					3	
any non-conformit which does not co r of the Parties or t dation, technical no	mply with by a thire otice.)	th d party	int			
Ntry Jurisd R W98PDL	Not Li	Control L sted			2	
				MOD N°	_	
CUSTOMER DRAWING						
iinium Plug 8D series						
r	NPRDS / PROJECT 859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N° V98PDL-C				SHEET 2/2		
B			A			