

FF1(300)-240X20MT0800

Aliases (UFSFF1030ET080)

KEMET, FF1, Flex Suppressors, Noise Suppression



Click here for the 3D model.

Dimensions	l ,
Sheet Size	240mmx20M
L	20000mm NOM
W	240mm NOM
Т	0.3mm NOM

Packaging Specifications	
Tape Description	Without PET Tape (Txx00)
Tape Thickness	0.03mm
Component Weight	4536.96 g

General Information		
Series	FF1	
Style	Sheet	
Description	Flex Suppressor Flame Retardant Type	
Features	Flame Retardant Type	
RoHS	Yes	
Qualifications	UL94 V-0, UL File No.E176124, AEC-Q200	
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free	

Specifications	
Temperature Range	-40/+125°C
Permeability	100 u At 3MHz
Effective Frequency	1 MHz to 3GHz
Specific Gravity	3.1TYP
Thermal Conductivity	1.36 typical
Surface Resistivity	1 MOhm/sq. TYP

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.